

ELEVATED WORK PLATFORM HIRE

SPECIFICATION SHEET

SCISSOR LIFT

18m/53ft DIESEL

SPECIFICATIONS

MEASUREMENTS

Working height max	18.15 m
A Platform height max	16.15 m
B Platform height - stowed	2.02 m
C Platform length:	3.98 m
outside, extended-single deck	5.34 m
D outside, extended-dual deck	6.57 m
E Slide-out platform extension deck - front	1.52 m
F Slide-out platform extension deck - rear	1.22 m
G Platform width - outside	1.83 m
H Height: stowed	3.15 m
stowed - rails lowered	2.47 m
I Length with outriggers	4.88 m
Length - extended: single deck	5.40 m
dual deck	6.57 m
J Width	2.29 m
K Wheelbase	2.84 m
L Ground clearance - center	.36 m

PRODUCTIVITY

Maximum platform occupancy	6
Lift capacity	680 kg
Capacity - extension deck	227 kg
Drive height	9.14 m
Speed - stowed	8.0 km/h
Drive speed - raised	1.1 km/h
Gradeability - stowed	40%
Maximum outrigger leveling: front to back	7°
side to side	12°
Turning radius - inside	2.16 m
Turning radius - outside	5.33 m
Drive	four wheel
Raise / lower speed	55 / 49 sec
Tires - foam-filled rough terrain	30 x 84 cm

WEIGHT

with outriggers	7574kg
-----------------	--------

